

DFO9200 19" x 2U Chassis Ethernet Cards



FEATURES

- * 19" x 2U Chassis Frame with 2 PSU
- * Supports 16 Ethernet 10/100Mbps and/or 10/100/1000Mbps Trx Cards
- * Power Supply input Voltage 100~240VAC, 50~60HZ
- * Over Voltage, Over Current, Short Circuit protection on power supplies
- * Compliance with CE, FCC, ROHS

APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)

ORDERING INFORMATION

DFO9200-2 19" x 2U Chassis Frame, 16 Slots, 2 Power Supplies, 100~240V, 50~60HZ

Electrical Parameters

Power Supply Input Voltage: 100~240VAC, 50~60HZ
 Direct Current: 5VDC
 Ripple: ≤50mV
 Noise: ≤50mV

Mechanical Parameters

External dimensions: 19"(485mm), 12.6"(320mm),
 W x D x H 3.5"(90mm)

Environmental Parameters

Operating temperature: -10°~50°
 Storage temperature: -20°~70°
 Relative humidity: 5%~95%
 Non-condensing

Regulatory Compliance: CE, FCC, ROHS

Manufactured to: ISO9001:2000 Standards

