DHA4800 HD/IP Hybrid Video Recorder 16ch H.264/H.264 4HDD



DESCRIPTION

The DHA4800 Series are Linux OS, Hybrid HD-AHD/TVI/CVI/CVBS/IP Digital Video Recorder appliances with 16ch HD/Analog inputs, or up to 24ch IP Video, 4 Audio, H.264/H.264 decoding, dual configurable video streams and G.711 audio compression for unrivaled quality and storage cost performance. Units feature: 1xHDMI (3840x2160, 1xHDMI (1920x1080) 1xVGA, 1xTV ports, 1x1000Mbps ports, 4 SATA HDD slots, up to 16 Alarms in/6 out, RS-232, RS-422, RS-485, 3 USB, 1 eSATA ports, all channels record and playback @1080p resolution and intelligent analytics. With Video Management via Server, PC Client, Web, Smart Phone Interface and ONVIF. The DHA4800 are ideal solutions for medium to large scale commercial and industrial HD and/or Network Video Surveillance installations.



- * Hybrid HD-AHD/TVI/CVI/CVBS and IP HDVR w/LINUX OS; dual H.264 Video compression
- * G.711 Audio compression; record with video
- * 16ch Video; 4 Audio; Duplex Talk channel
- * 24ch IP Video Inputs each channels @ 5MP
- * 2 x HDMI 1080p, 1xVGA, 1xBNC TV Monitor
- * 4 HDD Slots with 8TB each 32TB total
- * Pentaplex functions simultaneously record, display, playback, transmit files over network
- * All 16 channels recording @ 1080p resolution
- * 96Mbps incoming total capacity Bandwidth
- * 3D Intelligence, Privacy mask, Motion detect
- * 1 x RJ-45 1000Mbps Ethernet Data Ports
- * RS-232 for DVR Control; RS-422 PTZ Control
- * 3 USB (2.0) Ports Mouse / Backup; 1 eSATA
- * 16 Alarm in/6 Relay out/4 Audio in/1 out
- * Smart Phone Interface: iPhone and Android
- * HDD hibernation, fault Alarm, 128 Access Users
- * Compliance with CE, FCC, ROHS, ONVIF


ORDERING INFORMATION



APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)







DHA4816VA-5 Hybrid HD-AHD/TVI/CVI/CVBS/IP Digital Video Recorder 16 HD/Analog; or up to 24 IP Video, 4 Audio, 16 Alarms/6 Relays, 100-240VAC





DHA4800 HD/IP Hybrid Video Recorder 16ch H.264/H.264 4HDD



Electrical Specifications

Video Standards:
Video Compression:
Video Inputs Analog:
Video Inputs IP:
Video Outputs:
Video Playback:
Motion Detection:
Audio compression:
Audio Inputs:

Audio Talk:
Audio Input Impedance
Audio Output Impedance:
Audio Input (voice):
Audio Output (voice):
Audio Recording:
Backup Mode:
Data Ports

LAN Interface: USB Interfaces: Data Interfaces: PTZ Protocols/Baud: Alarms:

Pre Alarm Recording: Post Alarm Recording:

HD-AHD/TVI/CVI/CVBS/IP Dual H.264 VBR/CBR 16 BNC 1V p-p 75 Ohm 24 all @ 5MP 2 x HDMI, VGA, TV BNC

24 all @ 5MP 2 x HDMI, VGA, TV BNC 1/2/4/9/16 per screen 396 max Zones (22x18) G.711

4 via BNC Mic. in / Mic. out $30 K\Omega$) 4/8/16 channels BNC - 200-3000mV, $5 K\Omega$ BNC - 200-2800mV, $30 K\Omega$

BNC - 200-2000mV, 5KΩ BNC - 200-3000mV, 5KΩ Synchronous with Video USB, eSATA & Network

1xRJ-45 Port 1000 Mbps 3 Ports - Mouse, Backup RS-232, RS-422 and RS-485 Pelco D, 2400

16 In, 6 Relay outputs (max) 30 seconds

1-120 min. 60 min default

HDD and Management

Available HDD: HDD Management:

4HDDs – max 32TB Storage Hibernation, Fault Alarm,

Operating System

Real Time Operating System: Protocols Supported:

ipported: HTTP, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DDNS, PPPoE, E-Mail, FTP

Mechanical Specifications Dimension (H x W X D):

Rack mountable Weight not including H/D:

Environmental Specifications

Temperature: Humidity: Mean Time Between Failure (MTBF): Power Supply

Power Consumption:

Regulatory Compliance: Manufactured to:

Linux based

76mm x 440mm X417mm 3"(1.5U) x 17.3" x 16.5" 19" (with ears) Net 13.5 lb. (6Kg)

Gross 15.7 lb. (7Kg)

32° F~122° F, 0°C~50°C 10~90% non condensing

50,000 hours 100-240VAC, 50/60Hz max.30W (16ch)

CE, FCC, ROHS, ONVIF ISO9001:2000 Standard

