

DLV6230

TFT LCD Color Monitors

NTSC/PAL/VGA 15", 17", 19"



DESCRIPTION

The DLV6230 Series are high resolution, 15", 17" and 19" LCD Color Monitors compatible with NTSC/PAL Composite video and HDMI or VGA video signals. Units feature 2 BNC Video Inputs, 1 output, HDMI and VGA outputs. Additionally, all versions provide on screen (OSD) set-up and adjustment of parameters via controls conveniently located on the front panel. Available with 12VDC input voltages, the DLV6230 Series provide quality, high resolution images and are serious solutions for commercial and industrial legacy or IP based video surveillance installations.



FEATURES

- * NTSC/PAL TFT LCD Color Monitors
- * 750 TVL Resolution Composite Video
- * 2 BNC Video Input 1 BNC output
- * 1 x VGA and 1 x HDMI inputs
- * On Screen Display OSD function
- * Slim Lightweight, Space Saving Design
- * Stylish Metal Cabinets, 15", 17" and 19"
- * Remote Controller; Input Voltage 12VDC
- * Regulatory Compliance with CE, FCC, ROHS

APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)

ORDERING INFORMATION

DLV6230-15-1	NTSC/PAL/VGA, LCD Color Monitor 15", 1024x768 Resolution, 12VDC
DLV6230-17-1	NTSC/PAL/VGA, LCD Color Monitor 17", 1280x1024 Resolution, 12VDC
DLV6230-19-1	NTSC/PAL/VGA, LCD Color Monitor 19", 1280x1024 Resolution, 12VDC
DLV6230-19-8	NTSC/PAL/VGA, LCD Color Monitor 19", 1280x1024 Resolution, 220VAC

Electrical Parameters

Input Voltage:	12VDC
Power Consumption:	25W(15"); 32W(17") 35W(19")
Resolution 15":	1024x768
Resolution 17", 19":	1280x1024
Pixel Pitch 15", 17":	0.264mm x 0.264mm
19"	0.294mm x 0.294mm
Contrast Ratio 15":	800:1
Contrast Ratio 17":	1000:1
Contrast Ratio 19":	1500:1
Angle of View (all):	170° (H), 170° (V)
Brightness:	400cd/m ² - 15" 450cd/m ² - 17" and 19"
Response Time (all):	6ms

General Parameters

Composite Video: 2 BNC input; 1 output

# of Channels Displayed:	2
Composite Resolution:	750TVL, 75Hz
VGA:	15 pin mini Sub D
HDMI:	All

Environmental Parameters

Operating Temperature:	0°C~50°C
Operating Humidity:	5-95% noncondens.

Mechanical Parameters

Dimensions W x H x D:	
15":	14"(354mm), 11"(279mm), 2.67"(68mm)
17":	15.3"(389mm), 12.7"(322mm), 2.64"(67mm)
19":	16.7"(425mm), 13.8"(350mm), 2.7"(69mm)
Weight 15":	10 lbs(4.5Kg)
Weight 17":	11.2 lbs(5Kg)
Weight 19":	15.8 lbs(7Kg)

Regulatory Compliance: CE, FCC, ROHS

Manufactured to: ISO9001:2000

