

DNZ1875ZWB 4MP Explosion-Proof D/N IR Camera NDAA/Analytics



DESCRIPTION

The DNZ1875ZWB Series are 1/2.8" CMOS, 4MP Network-ready; **NDAA Compliant** Day/Night IR Cameras. Units are designed with high quality Encoder H.265/H.264 video compression and configurable triple stream outputs at 50/60fps 4MP (2592x1520). 1080p, 720p, resolution modes are available providing outstanding quality images under low illumination – Color 0.03Lux/F1.6/0Lux/IR LED on – 50m/100m night vision. Features include ICR, 3DNR, AGC, BLC, AWB, WDR and SD card slot (256GB). Configured with motorized 2.7-13.5mm or 5-50mm zoom lenses, Audio in/out, Alarm in/out, Smart Phone Interface, ONVIF and IP68. With 12VDC/POE, the Series 4MP DNZ1875ZWB Explosion Proof, IR Cameras are ideal solutions for demanding commercial, industrial and environmental IP video surveillance installations.

FEATURES

- * Network 4MP, Explosion-Proof IR Cameras
- * 1/2.8" CMOS Progressive Scan Image Sensor
- * Illumination Color 0.03Lux/F1.6/0Lux/IR LED on
- * H.265/H.264 Triple Stream configurable
- * Supports 50/60fps @ 4MP, 1080p Resolution
- * Analytics as Tripwire, Intrusion, Loitering
- * 2.7-13.5mm or 5-50mm Motorized Lenses
- * IR LEDs for Night Vision – 50/100 meters
- * 10/100Mbps Ethernet Compatible RJ-45 Port
- * Audio in/out; Alarm in/out; SD Card (256GB)
- * Smart Phone: iPhone and Android in NVR
- * Stainless Steel 316L Housing; DEFOG
- * Available with input Voltage 12VDC/POE
- * Certified: Gas Zones 1/2, Dust Zone 21/22 EX db IIC, T6 Gb/EX tb IIIC, T80°C Db, IP68
- * Compliance with CE, FCC, ONVIF, **NDAA**

ORDERING INFORMATION

DNZ1875ZW-24B 4MP, D/N Explosion-Proof, SS316L IR Camera, 2.7-13.5mm, 50m, 12VDC/POE

DNZ1875ZW-R4B 4MP, D/N Explosion-Proof, SS316L IR Camera, 5-50mm, 100m, 12VDC/POE

DZ6700-55A Steel wall mount + swivel bracket

DZ6750-55A Steel wall mount _ swivel + pole mount bracket



APPLICATIONS

- * Homeland Security
- * Petrochemical Industry
- * Hazardous Environments
- * Mining and Manufacturing
- * Corrosive Environments
- * Marine Environments
- * Government and Military
- * Power Generating Plants



DNZ1875ZWB

4MP Explosion-Proof D/N IR Camera NDAA/Analytics



DNZ1875ZWB	Product Specifications
Image Sensor:	4MP 1/2.8" Progressive Scan CMOS Image Sensor
Effective Pixels:	2592(H)×1520(V)
Minimum Illumination:	Color 0.03LUX/F1.6 / 0Lux(IR ON)
S/N Ratio:	> 55 dB
Dynamic Range:	True WDR 120dB
Auto Iris Control:	DC only
Lens /IR Night Vision:	2.7-13.5mm 50m or 5-50mm 100m IR LED ON
Digital Signal Processing:	High End Encoder with Reset Function
Video Compression:	H.265/H.264, Triple Stream, Configurable
Video Resolution:	4MP (2592 x 1520), 1080p, 720p, D1, CIF
Video Frame Rate:	50/60fps @ 4MP
Features:	ICR, 3DNR, AGC, BLC, AWB, WDR, DEFOG
Network Interface:	10/100 Mbps RJ-45 Port
Network Protocol:	HTTP, TCP/IP, ARP, IGMP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, SNMP
Smart Phone/Appliance:	iPhone, iPad, Android in NVR
Web Server:	Intuitive Browser Interface
CPU Requirement/OS:	Intel Core i7 2.4GHz/Embedded Linux OS; Compatible with DNE2404 (NDAA), DNE3800 (NDAA) NVR Series and , DNE9000-VMS Series; WIN8, WIN 10 Servers
Micro SD Card Slot:	Supports Local Recording - max 256GB
Power Supply:	12VDC - 12W (IR ON); Power over Ethernet
Operating Temperature:	-22°F ~ 140°F (-30°C ~ 60°C)
Operating Humidity:	0-95% non-condensing
Dimensions L x Dia. x H:	6.3" (160mm) X 10.7" (271mm, 6.5" (166mm)
Weight:	12.3 lb. (5.6 Kg)
Materials:	Stainless Steel 316L Materials; Explosion-Proof
Regulatory Compliance:	CE, FCC, ONVIF, IP68, NDAA
Certified as:	Gas zones1 & 2, dust zones 21 & 22, EX dB IIC T6 Gb, Ex tb IIIC, T80°C Db

